



## STEEL SHEET and COIL



### Hot Rolled

Commercial Steel –

Flat - Dry

- Pickled & Oiled

Coils

1050

SCS®

SHEET  
STRAPPING

### High Strength Low Alloy

Cor-Ten® or ASTM A 606

Ex-Ten® H50 or ASTM A 1011

DOMEX® 100XF

SCS®

### Cold Rolled

Commercial Steel

Flat

Coil

Drawing Steel

Flat

Coil

### Coated

Aluminized

Corrugated Galvanized

Electro-Galvanized

Galvanized

Flat

Coil

Galvannealed

Paintgrip Galvanized

Paintlok® or ASTM A 879

### Strapping



## STEEL SHEET HOT ROLLED

### ASTM A 1011 CS Type B\* Commercial Steel, Dry

Gage & Size in Inches	Est. Lbs. Per Sheet	Gage & Size in Inches	Est. Lbs. Per Sheet
<b>14 Ga. (.0747) 3.125 # Sq. Ft.</b>		<b>10 Ga. (.1345) 5.625 # Sq. Ft.</b>	
36 x 96	75.00	36 x 96	135.0
36 x 120	93.75	36 x 120	168.8
36 x 144	112.5	36 x 144	202.5
48 x 96	100.0	48 x 96	180.0
48 x 120	125.0	48 x 120	225.0
48 x 144	150.0	48 x 144	270.0
60 x 96	125.0	60 x 96	225.0
60 x 120	156.3	60 x 120	281.3
60 x 144	187.5	60 x 144	337.5
<b>12 Ga. (.1046) 4.375 # Sq. Ft.</b>		72 x 96	270.0
36 x 96	105.0	72 x 120	337.5
36 x 120	131.3	72 x 144	405.0
36 x 144	157.5	72 x 240	675.0
48 x 96	140.0	84 x 240	788.0
48 x 120	175.0	96 x 240	900.0
48 x 144	210.0	<b>9 Ga. (.1495) 6.25 # Sq. Ft.</b>	
60 x 96	175.0	48 x 120	250.0
60 x 120	218.8	<b>8 Ga. (.1644) 6.875 # Sq. Ft.</b>	
60 x 144	262.5	48 x 96	220.0
72 x 96	210.0	48 x 120	275.0
72 x 120	262.5	60 x 96	275.0
72 x 144	315.0	60 x 120	343.8
84 x 240	613.0	<b>7 Ga. (.1793) 7.500 # Sq. Ft.</b>	
<b>11 Ga. (.1196) 5.000 # Sq. Ft.</b>		36 x 96	180.0
36 x 96	120.0	36 x 120	225.0
36 x 120	150.0	36 x 144	270.0
48 x 96	160.0	48 x 96	240.0
48 x 120	200.0	48 x 120	300.0
48 x 144	240.0	48 x 144	360.0
60 x 96	200.0	60 x 96	300.0
60 x 120	250.0	60 x 120	375.0
60 x 144	300.0	60 x 144	450.0
72 x 96	240.0	72 x 96	360.0
72 x 120	300.0	72 x 120	450.0
72 x 144	360.0	72 x 144	540.0
96 x 240	800.0	Over 72" See Plates, page 15	

\*.10 max. carbon

# STEEL SHEET HOT ROLLED PICKLED AND OILED



## ASTM A 1011 CS Type B\* Commercial Steel

Gage & Size in Inches	Est. Lbs. Per Sheet	Gage & Size in Inches	Est. Lbs. Per Sheet
<b>14 Ga. (.0747) 3.125 # Sq. Ft.</b>		<b>11 Ga. (.1196) 5.000 # Sq. Ft.</b>	
36 x 96	75.00	60 x 120	250.0
36 x 120	93.75	60 x 144	300.0
36 x 144	112.5	72 x 96	240.0
48 x 96	100.0	72 x 120	300.0
48 x 120	125.0	72 x 144	360.0
48 x 144	150.0	<b>10 Ga. (.1345) 5.625 # Sq. Ft.</b>	
60 x 96	125.0	36 x 96	135.0
60 x 120	156.3	36 x 120	168.8
60 x 144	187.5	48 x 96	180.0
<b>13 Ga. (.0897) 3.750 # Sq. Ft.</b>		48 x 120	225.0
36 x 96	90.00	48 x 144	270.0
36 x 120	112.5	60 x 96	225.0
48 x 96	120.0	60 x 120	281.3
48 x 120	150.0	60 x 144	337.5
60 x 120	187.5	72 x 96	270.0
<b>12 Ga. (.1046) 4.375 # Sq. Ft.</b>		72 x 120	337.5
36 x 96	105.0	72 x 144	405.0
36 x 120	131.3	<b>9 Ga. (.1495) 6.25 # Sq. Ft.</b>	
48 x 96	140.0	48 x 96	200.0
48 x 120	175.0	48 x 120	250.0
48 x 144	210.0	<b>8 Ga. (.1644) 6.875 # Sq. Ft.</b>	
60 x 96	175.0	48 x 96	220.0
60 x 120	218.8	48 x 120	275.0
60 x 144	262.5	<b>7 Ga. (.1793) 7.500 # Sq. Ft.</b>	
72 x 96	210.0	36 x 96	180.0
72 x 120	262.5	36 x 120	225.0
72 x 144	315.0	36 x 144	270.0
<b>11 Ga. (.1196) 5.000 # Sq. Ft.</b>		48 x 96	240.0
36 x 96	120.0	48 x 120	300.0
36 x 120	150.0	48 x 144	360.0
48 x 96	160.0	60 x 96	300.0
48 x 120	200.0	60 x 120	375.0
48 x 144	240.0	60 x 144	450.0
60 x 96	200.0	72 x 96	360.0
<b>11 Ga. (.1196) 5.000 # Sq. Ft.</b>		72 x 120	450.0
36 x 96	120.0	72 x 144	540.0
36 x 120	150.0	<b>6 Ga. (.1943) 8.125 # Sq. Ft.</b>	
48 x 96	160.0	48 x 96	260.0
48 x 120	200.0	48 x 120	325.0
48 x 144	240.0		
60 x 96	200.0		

\*.10 max. carbon

# STEEL SHEET AISI/SAE 1050 HOT ROLLED, DRY



Identification Color: Yellow

Gage & Size in Inches	Est. Lbs. Per Sheet	Gage & Size in Inches	Est. Lbs. Per Sheet
<b>12 Ga. (.1046) 4.375 # Sq. Ft.</b>		<b>10 Ga. (.1345) 5.625 # Sq. Ft.</b>	
40 x 120	149.5	40 x 120	187.5
<b>11 Ga. (.1196) 5.000 # Sq. Ft.</b>		<b>7 Ga. (.1793) 7.500 # Sq. Ft.</b>	
40 x 120	166.7	40 x 120	250.0



## STEEL SHEET HOT ROLLED SCS® ††

### Commercial Steel

#### EX-TEN® H50 or ASTM A 1011 HSLAS‡ Gr. 50 Class 1

The SCS process cleans as-rolled (HR) material to produce an extremely clean surface, which approximates a cold rolled finish that also resists rust without oil or preservatives.

Identification Colors: Commercial Steel — No Paint  
Ex-Ten or A 1011 — Orange

Gage & Size in Inches	Est. Lbs. Per Sheet	CS	Ex-Ten or ASTM A 1011
<b>14 Ga. (.0747) 3.125 # Sq. Ft.</b>			
48 x 96	100.0	X	..
48 x 120	125.0	..	X
60 x 120	156.3	X	..
60 x 144	187.5	X	..
<b>12 Ga. (.1046) 4.375 # Sq. Ft.</b>			
48 x 96	140.0	X	..
48 x 120	175.0	X	..
60 x 120	218.8	X	X
60 x 144	262.5	X	..
72 x 120	262.5	X	..
72 x 144	315.0	X	..
<b>11 Ga. (.1196) 5.000 # Sq. Ft.</b>			
48 x 120	200.0	X	..
60 x 120	250.0	X	..
60 x 144	300.0	X	..
72 x 144	360.0	X	..
<b>10 Ga. (.1345) 5.625 # Sq. Ft.</b>			
48 x 120	225.0	X	..
60 x 120	281.3	X	..
60 x 144	337.5	..	X
72 x 120	337.5	X	..
72 x 144	405.0	X	..
<b>7 Ga. (.1793) 7.500 # Sq. Ft.</b>			
48 x 96	240.0	X	..
48 x 120	300.0	X	X
60 x 120	375.0	X	..
72 x 96	360.0	X	..

For SCS Plates, see page 18

\* Other sizes and grades are available upon request

† A patented process of The Material Works, Ltd.

‡ HSLAS - High Strength Low Alloy Steel

## STEEL SHEET HIGH STRENGTH LOW ALLOY



**COR-TEN® A or ASTM A 606 Type 4**  
**EX-TEN® H50 or ASTM A 1011 HSLAS\* Gr. 50 Class 1**

Identification Colors: Cor-Ten — Pink; Ex-Ten — Orange

Gage & Size in Inches	Est. Lbs. Per Sheet	Cor-Ten	Ex-Ten
<b>14 Ga. (.0747) 3.125 # Sq. Ft.</b>			
48 x 120	125.0	X	X
48 x 144	150.0	X	..
<b>12 Ga. (.1046) 4.375 # Sq. Ft.</b>			
48 x 96	140.0		X
48 x 120	175.0	X	X
48 x 144	210.0	X	..
60 x 96	175.0	..	X
60 x 120	218.8	X	X
<b>11 Ga. (.1196) 5.000 # Sq. Ft.</b>			
48 x 120	200.0	X	X
48 x 144	240.0	X	..
<b>10 Ga. (.1345) 5.625 # Sq. Ft.</b>			
48 x 96	180.0	X	..
48 x 120	225.0	X	X
48 x 144	270.0	X	..
60 x 120	281.3	X	X
60 x 144	337.5	X	X
<b>8 Ga. (.1644) 6.875 # Sq. Ft.</b>			
48 x 144	330.0	X	..
<b>7 Ga. (.1793) 7.500 # Sq. Ft.</b>			
48 x 96	240.0	X	X
48 x 120	300.0	X	X

\*HSLAS - High Strength Low Alloy Steel

## STEEL SHEET HIGH STRENGTH LOW ALLOY



**DOMEX® 100XF\***

Identification Color: Green and Black

Size in Inches	Est. Lbs. Per Sheet	Size in Inches	Est. Lbs. Per Sheet
<b>.0787 min. (3.464 # Sq. Ft.)</b>		<b>.120 nom. (5.018 # Sq. Ft.)</b>	
41 1/2 x 120	119.8	52 x 120	217.5
<b>.100 nom. (4.181 # Sq. Ft.)</b>		<b>.160 nom. (6.691 # Sq. Ft.)</b>	
41 1/2 x 120	144.6	60 x 120	334.6

\*Produced by SSAB.  
Other sizes are available upon request.



## STEEL SHEET COLD ROLLED

### ASTM A 1008 CS Type B Commercial Steel, Oiled

Gage & Size in Inches	Est. Lbs. Per Sheet	Gage & Size in Inches	Est. Lbs. Per Sheet
<b>26 Ga. (.0179) .750 # Sq. Ft.</b>		<b>16 Ga. (.0598) 2.500 # Sq. Ft.</b>	
48 x 120	30.00	48 x 96	80.00
		48 x 120	100.0
<b>24 Ga. (.0239) 1.000 # Sq. Ft.</b>		48 x 144	120.0
36 x 96	24.00	60 x 96	100.0
36 x 120	30.00	60 x 120	125.0
48 x 96	32.00	60 x 144	150.0
48 x 120	40.00	72 x 120	150.0
		72 x 144	180.0
<b>22 Ga. (.0299) 1.250 # Sq. Ft.</b>		<b>14 Ga. (.0747) 3.125 # Sq. Ft.</b>	
36 x 96	30.00	36 x 96	75.00
36 x 120	37.50	36 x 120	93.75
48 x 96	40.00	42 x 120	109.4
48 x 120	50.00	48 x 96	100.0
48 x 144	60.00	48 x 120	125.0
		48 x 144	150.0
<b>20 Ga. (.0359) 1.500 # Sq. Ft.</b>		60 x 96	125.0
36 x 96	36.00	60 x 120	156.3
36 x 120	45.00	60 x 144	187.5
36 x 144	54.00	72 x 120	187.5
48 x 96	48.00	72 x 144	225.0
48 x 120	60.00		
48 x 144	72.00	<b>13 Ga. (.0897) 3.750 # Sq. Ft.</b>	
60 x 96	60.00	36 x 96	90.00
60 x 120	75.00	36 x 120	112.5
60 x 144	90.00	48 x 96	120.0
		48 x 120	150.0
<b>19 Ga. (.0418) 1.750 # Sq. Ft.</b>		48 x 144	180.0
36 x 96	42.00	<b>12 Ga. (.1046) 4.375 # Sq. Ft.</b>	
48 x 96	56.00	36 x 96	105.0
48 x 120	70.00	36 x 120	131.3
		48 x 96	140.0
<b>18 Ga. (.0478) 2.000 # Sq. Ft.</b>		48 x 120	175.0
36 x 96	48.00	48 x 144	210.0
36 x 120	60.00	60 x 96	175.0
36 x 144	72.00	60 x 120	218.8
42 x 120	70.00	60 x 144	262.5
48 x 96	64.00	<b>11 Ga. (.1196) 5.000 # Sq. Ft.</b>	
48 x 120	80.00	36 x 96	120.0
48 x 144	96.00	36 x 120	150.0
60 x 96	80.00	48 x 96	160.0
60 x 120	100.0	48 x 120	200.0
		48 x 144	240.0
<b>16 Ga. (.0598) 2.500 # Sq. Ft.</b>		60 x 120	250.0
36 x 96	60.00	<b>10 Ga. (.1345) 5.625 # Sq. Ft.</b>	
36 x 120	75.00	36 x 96	135.0
36 x 144	90.00	36 x 120	168.8
		48 x 96	180.0
		48 x 120	225.0

## STEEL SHEET COLD ROLLED



### ASTM A 1008 DS Type B Drawing Steel Aluminum Killed

Non-Age Hardening, Oiled

Intended for difficult drawing, spinning, and forming operations.

Gage & Size in Inches	Est. Lbs. Per Sheet	Gage & Size in Inches	Est. Lbs. Per Sheet
<b>24 Ga. (.0239) 1.000 # Sq. Ft.</b>		<b>16 Ga. (.0598) 2.500 # Sq. Ft.</b>	
48 x 120	40.00	48 x 96	80.00
<b>22 Ga. (.0299) 1.250 # Sq. Ft.</b>		48 x 120	100.0
48 x 96	40.00	48 x 144	120.0
48 x 120	50.00	<b>14 Ga. (.0747) 3.125 # Sq. Ft.</b>	
<b>20 Ga. (.0359) 1.500 # Sq. Ft.</b>		36 x 96	75.00
36 x 96	36.00	36 x 120	93.75
36 x 120	45.00	48 x 96	100.0
48 x 96	48.00	48 x 120	125.0
48 x 120	60.00	48 x 144	150.0
<b>19 Ga. (.0418) 1.750 # Sq. Ft.</b>		<b>13 Ga. (.0897) 3.750 # Sq. Ft.</b>	
48 x 96	56.00	48 x 96	120.0
48 x 120	70.00	48 x 120	150.0
<b>18 Ga. (.0478) 2.000 # Sq. Ft.</b>		<b>12 Ga. (.1046) 4.375 # Sq. Ft.</b>	
36 x 96	48.00	48 x 96	140.0
36 x 120	60.00	48 x 120	175.0
48 x 96	64.00	<b>11 Ga. (.1196) 5.000 # Sq. Ft.</b>	
48 x 120	80.00	36 x 120	150.0
<b>16 Ga. (.0598) 2.500 # Sq. Ft.</b>		48 x 120	200.0
36 x 96	60.00	<b>10 Ga. (.1345) 5.625 # Sq. Ft.</b>	
36 x 120	75.00	36 x 120	168.8
		48 x 120	225.0

## STEEL SHEET IN COIL COLD ROLLED



### ASTM A 1008 CS Type B Commercial Steel, Oiled

Size in Inches Minimum	Stock Length	Size in Inches Minimum	Stock Length
<b>.017 x 48</b>	Coil	<b>.057 x 48</b>	Coil
<b>.023 x 36, 48</b>	Coil	<b>.070 x 36, 42, 48, 60</b>	Coil
<b>.028 x 36, 48</b>	Coil	<b>.085 x 36, 48</b>	Coil
<b>.033 x 36, 48, 60</b>	Coil	<b>.098 x 36, 48, 60</b>	Coil
<b>.038 x 36, 48</b>	Coil	<b>.114 x 36, 48, 60</b>	Coil
<b>.044 x 36, 42, 48, 60</b>	Coil	<b>.128 x 36, 48</b>	Coil
<b>.055 x 36, 48, 60</b>	Coil		



## STEEL SHEET IN COIL COLD ROLLED

### ASTM A 1008 DS Type B Drawing Steel Aluminum Killed Oiled

Intended for difficult drawing, spinning, and forming operations.

Size in Inches Minimum	Stock Length	Size in Inches Minimum	Stock Length
<b>.023 x 48</b>	Coil	<b>.070 x 36, 48</b>	Coil
<b>.028 x 48</b>	Coil	<b>.085 x 48</b>	Coil
<b>.033 x 36, 48</b>	Coil	<b>.098 x 48</b>	Coil
<b>.038 x 48</b>	Coil	<b>.114 x 36, 48</b>	Coil
<b>.044 x 36, 48</b>	Coil	<b>.128 x 36, 48</b>	Coil
<b>.055 x 36, 48</b>	Coil		



## STEEL SHEET IN COIL HOT ROLLED PICKLED AND OILED

### ASTM A 1011 CS Type B Commercial Steel

Size in Inches Minimum	Stock Length	Size in Inches Minimum	Stock Length
<b>.071 x 36, 48, 60</b>	Coil	<b>.112 x 36, 48, 60</b>	Coil
<b>.083 x 36, 48, 60</b>	Coil	<b>.127 x 36, 48, 60</b>	Coil
<b>.097 x 36, 48, 60</b>	Coil		



**STEEL COIL  
GALVANIZED  
ASTM A 653 CS Type B**



Surface Chem. Treated  
G90 or G60 Coating\* Minimum Spangle  
Commercial Steel

Gage & Size in Inches	G90*	G60*
<b>26 Ga. (.0217) .906 # Sq. Ft.</b>		
48 x Coil	X	X
60 x Coil	X	..
<b>24 Ga. (.0276) 1.156 # Sq. Ft.</b>		
36 x Coil	X	..
48 x Coil	X	X
50 x Coil	..	X
60 x Coil	X	..
<b>22 Ga. (.0336) 1.406 # Sq. Ft.</b>		
36 x Coil	X	..
48 x Coil	X	X
60 x Coil	X	..
<b>20 Ga. (.0396) 1.656 # Sq. Ft.</b>		
36 x Coil	X	..
48 x Coil	X	X
60 x Coil	X	..
<b>18 Ga. (.0516) 2.156 # Sq. Ft.</b>		
36 x Coil	X	..
48 x Coil	X	X
60 x Coil	X	..
<b>16 Ga. (.0635) 2.656 # Sq. Ft.</b>		
36 x Coil	X	..
48 x Coil	X	X
60 x Coil	X	..
<b>14 Ga. (.0785) 3.281 # Sq. Ft.</b>		
36 x Coil	X	..
48 x Coil	X	..
60 x Coil	X	..
<b>12 Ga. (.1084) 4.531 # Sq. Ft.</b>		
36 x Coil	X	..
48 x Coil	X	..
60 x Coil	X	..
<b>11 Ga. (.1233) 5.156 # Sq. Ft.</b>		
48 x Coil	X	..
60 x Coil	X	..
<b>10 Ga. (.1382) 5.781 # Sq. Ft.</b>		
36 x Coil	X	..
48 x Coil	X	..

\*UL® (Underwriters Laboratories Inc.) approval available.  
Can be selected to comply to RoHS.



## STEEL SHEET GALVANIZED

**ASTM A 653 CS Type B G90**

Surface Chem. Treated

G90 Coating\* Minimum Spangle

Commercial Steel

Gage & Size in Inches	Est. Lbs. Per Sheet	Gage & Size in Inches	Est. Lbs. Per Sheet
<b>26 Ga. (.0217) .906 # Sq. Ft.</b>		<b>16 Ga. (.0635) 2.656 # Sq. Ft.</b>	
48 x 96	28.99	36 x 96	63.74
48 x 120	36.24	36 x 120	79.68
60 x 120	45.30	36 x 144	95.60
		48 x 96	84.99
		48 x 120	106.2
		48 x 144	127.5
		60 x 120	132.8
<b>24 Ga. (.0276) 1.156 # Sq. Ft.</b>		<b>14 Ga. (.0785) 3.281 # Sq. Ft.</b>	
36 x 96	27.74	36 x 96	78.74
36 x 120	34.68	36 x 120	98.43
48 x 96	36.99	36 x 144	118.1
48 x 120	46.24	48 x 96	105.0
48 x 144	55.49	48 x 120	131.2
60 x 120	57.80	48 x 144	157.5
		60 x 120	164.1
<b>22 Ga. (.0336) 1.406 # Sq. Ft.</b>		<b>12 Ga. (.1084) 4.531 # Sq. Ft.</b>	
36 x 96	33.74	36 x 96	108.7
36 x 120	42.18	36 x 120	135.9
48 x 96	44.99	48 x 96	145.0
48 x 120	56.24	48 x 120	181.2
60 x 120	70.30	48 x 144	217.5
		60 x 120	226.6
		60 x 144	271.9
<b>20 Ga. (.0396) 1.656 # Sq. Ft.</b>		<b>11 Ga. (.1233) 5.156 # Sq. Ft.</b>	
36 x 96	39.74	48 x 96	165.0
36 x 120	49.68	48 x 120	206.2
48 x 96	52.99	48 x 144	247.5
48 x 120	66.24		
48 x 144	79.49		
60 x 120	82.80		
<b>18 Ga. (.0516) 2.156 # Sq. Ft.</b>		<b>10 Ga. (.1382) 5.781 # Sq. Ft.</b>	
36 x 96	51.74	36 x 96	138.7
36 x 120	64.68	36 x 120	173.4
48 x 96	68.99	48 x 96	185.0
48 x 120	86.24	48 x 120	231.2
48 x 144	103.5	48 x 144	277.5
60 x 120	107.8	60 x 120	289.1
60 x 144	129.4		
		<b>8 Ga. (.1681) 7.031 # Sq. Ft.</b>	
		48 x 96	225.0
		48 x 120	281.2
		48 x 144	337.5

\*UL® (Underwriters Laboratories Inc.) approval available.  
Can be selected to comply to RoHS.



## STEEL SHEET AND COIL GALVANNEALED

ASTM A 653 CS Type B A60

A60 Coating\*  
Commercial Steel



A zinc-coated sheet which has been annealed after coating. In this way the spelter is fused to the base metal, and the result is a zinc coating which cannot be flaked or peeled in forming. The surface is readily painted without preliminary treating.

Gage & Size in Inches	Est. Lbs. Per Sheet	Gage & Size in Inches	Est. Lbs. Per Sheet
<b>24 Ga. (.0276) 1.156 # Sq. Ft.</b>		<b>16 Ga. (.0635) 2.656 # Sq. Ft.</b>	
48 x Coil		36 x Coil	
48 x 96	36.99	36 x 96	63.74
48 x 120	46.24	36 x 120	79.68
		48 x Coil	
		48 x 96	84.99
		48 x 120	106.2
		48 x 144	127.5
<b>22 Ga. (.0336) 1.406 # Sq. Ft.</b>		60 x Coil	
48 x Coil		60 x 120	132.8
48 x 96	44.99	60 x 144	159.4
48 x 120	56.24		
48 x 144	67.49		
<b>20 Ga. (.0396) 1.656 # Sq. Ft.</b>		<b>14 Ga. (.0785) 3.281 # Sq. Ft.</b>	
36 x Coil		36 x Coil	
36 x 96	39.74	36 x 120	98.43
36 x 120	49.68	48 x Coil	
48 x Coil		48 x 96	105.0
48 x 96	52.99	48 x 120	131.2
48 x 120	66.24	48 x 144	157.4
48 x 144	79.49	60 x Coil	
		60 x 120	164.1
		60 x 144	196.9
<b>18 Ga. (.0516) 2.156 # Sq. Ft.</b>		<b>12 Ga. (.1084) 4.531 # Sq. Ft.</b>	
36 x Coil		48 x Coil	
36 x 96	51.74	48 x 96	145.0
36 x 120	64.68	48 x 120	181.2
36 x 144	77.62	60 x Coil	
48 x Coil		60 x 120	226.6
48 x 96	68.99	60 x 144	271.9
48 x 120	86.24		
48 x 144	103.5		
60 x Coil		<b>11 Ga. (.1233) 5.156 # Sq. Ft.</b>	
60 x 96	86.24	48 x Coil	
60 x 120	107.8	48 x 120	206.2

\*UL® (Underwriters Laboratories Inc.) approval available



**STEEL SHEET AND COIL  
ELECTRO-GALVANIZED  
PAINTLOK® OR ASTM A 879 CS**



Phosphate Treated

Dry

Gage & Size in Inches	Est. Lbs. Per Sheet	Gage & Size in Inches	Est. Lbs. Per Sheet
<b>26 Ga. (.0179) .750 # Sq. Ft.</b>		<b>18 Ga. (.0478) 2.000 # Sq. Ft.</b>	
48 x Coil		36 x Coil	
48 x 96	24.00	36 x 96	48.00
48 x 120	30.00	36 x 120	60.00
<b>24 Ga. (.0239) 1.000 # Sq. Ft.</b>		48 x Coil	
48 x Coil		48 x 96	64.00
48 x 96	32.00	48 x 120	80.00
48 x 120	40.00	<b>16 Ga. (.0598) 2.500 # Sq. Ft.</b>	
<b>22 Ga. (.0299) 1.250 # Sq. Ft.</b>		36 x Coil	
36 x Coil		36 x 96	60.00
36 x 96	30.00	36 x 120	75.00
36 x 120	37.50	48 x Coil	
48 x Coil		48 x 96	80.00
48 x 96	40.00	48 x 120	100.0
48 x 120	50.00	48 x 144	120.0
48 x 144	60.00	<b>14 Ga. (.0747) 3.125 # Sq. Ft.</b>	
<b>20 Ga. (.0359) 1.500 # Sq. Ft.</b>		36 x Coil	
36 x Coil		36 x 96	75.00
36 x 96	36.00	36 x 120	93.75
36 x 120	45.00	48 x Coil	
48 x Coil		48 x 96	100.0
48 x 96	48.00	48 x 120	125.0
48 x 120	60.00		



## STEEL SHEET AND COIL ALUMINIZED

**ASTM A 463 Type 1**  
Coating T1-40, Oiled



Aluminized Steel is sheet steel coated with aluminum by a patented hot-dip process. The finished product, coated on both sides, combines the surface characteristics of aluminum with the mechanical properties of steel.

**Type # 1 - Aluminum-silicon alloy coating used for its high heat reflectivity and resistance to a combination of heat and corrosion.**

Gage & Size in Inches	Est. Lbs. Per Sheet	Gage & Size in Inches	Est. Lbs. Per Sheet
<b>22 Ga. (.0336) 1.363 # Sq. Ft.</b>		<b>18 Ga. (.0516) 2.113 # Sq. Ft.</b>	
36 x Coil		48 x 120	84.52
36 x 96	32.72	60 x Coil	
36 x 120	40.89	60 x 120	105.65
48 x Coil		60 x 144	126.8
48 x 96	43.62	<b>16 Ga. (.0635) 2.613 # Sq. Ft.</b>	
48 x 120	54.52	36 x Coil	
<b>20 Ga. (.0396) 1.613 # Sq. Ft.</b>		36 x 96	62.71
36 x Coil		36 x 120	78.39
36 x 96	38.71	48 x Coil	
36 x 120	48.39	48 x 96	83.62
48 x Coil		48 x 120	104.5
48 x 96	51.62	60 x Coil	
48 x 120	64.52	60 x 120	130.7
60 x Coil		60 x 144	156.8
60 x 120	80.65	<b>14 Ga. (.0785) 3.238 # Sq. Ft.</b>	
60 x 144	96.78	48 x Coil	
<b>18 Ga. (.0516) 2.113 # Sq. Ft.</b>		48 x 120	129.5
36 x Coil		48 x 144	155.4
36 x 96	50.71	60 x Coil	
36 x 120	63.39	60 x 120	161.9
48 x Coil		<b>12 Ga. (.1084) 4.488 # Sq. Ft.</b>	
48 x 96	67.62	48 x Coil	
		48 x 96	143.6
		48 x 120	179.5
		48 x 144	215.4
		60 x Coil	
		60 x 120	224.4
		60 x 144	269.3



## STEEL SHEET AND COIL PAINTGRIP GALVANIZED

ASTM A 653 CS Type B G90

Minimum Spangle, Dry  
G90 Coating\* Commercial Steel



The surface has a full zinc coating and is phosphate treated for painting. Recommended for forming.

Gage & Size in Inches	Est. Lbs. Per Sheet	Gage & Size in Inches	Est. Lbs. Per Sheet
<b>26 Ga. (.0217) .906 # Sq. Ft.</b>		<b>16 Ga. (.0635) 2.656 # Sq. Ft.</b>	
36 x 96	21.74	36 x Coil	
36 x 120	27.18	36 x 96	63.74
<b>24 Ga. (.0276) 1.156 # Sq. Ft.</b>		36 x 120	79.68
48 x Coil		48 x Coil	
48 x 96	36.99	48 x 96	84.99
48 x 120	46.24	48 x 120	106.2
<b>22 Ga. (.0336) 1.406 # Sq. Ft.</b>		60 x Coil	
48 x Coil		<b>14 Ga. (.0785) 3.281 # Sq. Ft.</b>	
48 x 120	56.24	48 x Coil	
<b>20 Ga. (.0396) 1.656 # Sq. Ft.</b>		48 x 96	105.0
48 x 96	52.99	48 x 120	131.2
48 x 120	66.24	60 x Coil	
<b>18 Ga. (.0516) 2.156 # Sq. Ft.</b>		<b>12 Ga. (.1084) 4.531 # Sq. Ft.</b>	
48 x Coil		48 x Coil	
48 x 96	68.99		
48 x 120	86.24		

\*UL® (Underwriters Laboratories Inc.) approval available



## STEEL SHEET CORRUGATED GALVANIZED

ASTM A 653 CS Type B G90

Surface Chem. Treated  
G90 Coating, Commercial Steel  
2 1/2" Corrugations

Gage & Size in Inches	Est. Lbs. Per Sheet	Gage & Size in Inches	Est. Lbs. Per Sheet
<b>26 Ga. (.0217)</b>		<b>20 Ga. (.0396)</b>	
27 1/2 x 144	27.18	27 1/2 x 96	33.12
<b>24 Ga. (.0276)</b>		27 1/2 x 120	41.40
27 1/2 x 120	28.90	27 1/2 x 144	49.68
<b>22 Ga. (.0336)</b>		<b>18 Ga. (.0516)</b>	
27 1/2 x 120	35.15	27 1/2 x 96	43.12
27 1/2 x 144	42.18	27 1/2 x 120	53.90

Corrugations run the length of sheet.

Other widths and lengths can also be furnished by corrugating material cut and flattened from coil.

## STEEL STRAPPING FLAT IN COIL

Painted and Waxed  
to ASTM D-3953, Type I, Finish A

Size in Inches	Average Break Strength in Lbs.	Ft. Per Lb.	Lbs. Per 1000 Ft.
<b>REGULAR DUTY* – Oscillated Wound</b>			
<b>1/2 x .020</b> .....	1180 .....	29.42 .....	34.00
<b>5/8 x .020</b> .....	1470 .....	23.53 .....	42.50
<b>3/4 x .020</b> .....	1770 .....	19.61 .....	50.99
<b>HIGH TENSILE* – Oscillated Wound</b>			
<b>3/4 x .023</b> .....	2470 .....	17.10 .....	58.64
<b>HIGH TENSILE – Ribbon Wound</b>			
<b>3/4 x .029**</b> .....	3325 .....	13.50 .....	75.19
<b>1 1/4 x .029*</b>	5400	8.10	123.3

\*105# average coils  
\*\*75# average coils