















## STEEL STRIP\* HOT ROLLED

Low Carbon Commercial Quality

### ASTM A 1011 CS Type B

Random Lengths 16 Ft.

Gage & Size in Inches	Lbs. Per Ft.	Est. Lbs. Per 16' Bar	Gage & Size in Inches	Lbs. Per Ft.	Est. Lbs. Per 16' Bar
<b>1/8 (.125) x</b>			<b>3/16 (.1875) x</b>		
1/2	.2125	3.400	1/2	.3188	5.101
5/8	.2656	4.250	5/8	.3984	6.374
3/4	.3188	5.101	3/4	.4781	7.650
7/8	.3719	5.950	7/8	.5578	8.925
<b>1</b>	.4250	6.800	<b>1</b>	.6375	10.20
<b>1 1/8</b>	.4781	7.650	<b>1 1/8</b>	.7172	11.48
<b>1 1/4</b>	.5313	8.501	<b>1 1/4</b>	.7969	12.75
<b>1 3/8</b>	.5844	9.350	<b>1 3/8</b>	.8766	14.03
<b>1 1/2</b>	.6375	10.20	<b>1 1/2</b>	.9563	15.30
<b>1 3/4</b>	.7438	11.90	<b>1 3/4</b>	1.116	17.86
<b>2</b>	.8500	13.60	<b>2</b>	1.275	20.40
<b>2 1/2</b>	1.063	17.01	<b>2 1/4</b>	1.434	22.94
<b>2 3/4</b>	1.169	18.70	<b>2 1/2</b>	1.594	25.50
<b>3</b>	1.275	20.40	<b>2 3/4</b>	1.753	28.05
<b>3 1/4</b>	1.381	22.10	<b>3</b>	1.913	30.61
<b>3 1/2</b>	1.488	23.81	<b>3 1/4</b>	2.072	33.15
<b>4</b>	1.700	27.20	<b>3 1/2</b>	2.231	35.70
<b>4 1/2</b>	1.913	30.61	<b>4</b>	2.550	40.80
<b>5</b>	2.125	34.00	<b>4 1/2</b>	2.869	45.90
<b>5 1/2</b>	2.338	37.41	<b>5</b>	3.188	51.01
<b>6</b>	2.550	40.80	<b>5 1/2</b>	3.506	56.10
<b>7</b>	2.975	47.60	<b>6</b>	3.825	61.20
<b>8</b>	3.400	54.40	<b>7</b>	4.463	71.41
			<b>8</b>	5.100	81.60
<b>10 Ga. (.134) x</b>			<b>10</b>	6.375	102.0
<b>1</b>	.4556	7.290	<b>12</b>	7.650	122.4
<b>1 1/2</b>	.6834	10.93			

\*Also available Pickled Dry or Oiled











